


RS9210

Programmable Thermostat
Multi-Stage – 2 Heat / 1 Cool

Robertshaw®



Description

Contractors can offer owners easy, yet powerful and reliable two-stage heating and one-stage cooling control in a simple, modern design with the RS9210 programmable wall thermostat.

Features and Benefits

- Quick, easy installation
- Modern, user-friendly design and operation
- 7-day, 5-1-1 or non-programmable
- Large, easy-to-read 4.6-square-inch blue backlit display
- Filter change reminder (selectable on/off)
- Adjustable temperature differential (swing)
- Heat pump-compatible: auxiliary/emergency heat

Specifications

Dimensions (W x H x D)	4.7 x 3.8 x 1 in. (119.6 x 97.6 x 26 mm)
Mounting	Wall or junction box
System compatibility	Two-stage heating and one-stage cooling
System fuel source	Gas, electric or oil
Heat pump compatibility	Systems with auxiliary or emergency heat
Millivolt application compatibility	Yes
Temperature range	41°F to 95°F (5°C to 35°C)
Control temperature range	44°F to 90°F (7°C to 32°C)
Display accuracy	±1°C (at 20°C) / ±1°F (at 68°F)
Power sources	24V AC (18 to 30V AC), 50/60 Hz for hardwire (common wire required) or 2 AAA 1.5V alkaline batteries (included)
Terminals	R, C, Y, W2, W/E, G, O, B

6 Year
Limited
Warranty

Robertshaw
RANCO • PARAGON • CASTFUTURA

Customer Service
+1 800 304 6563
HVACCustomerService
@robertshaw.com

Technical Service
+1 800 445 8299
TechnicalService
@robertshaw.com

www.robertshaw.com
©2024 Robertshaw
05/24 150-2798 RevB

Replacement and Cross Reference

RS9210

Pro1®	T725
Honeywell	TH6220D1028, TH4210U2002, TH2110DH1000, TH2210DV1006, TH4210D1005
Braeburn®	2220NC, 2200NC, 5020
Emerson™ White-Rodgers™	1F83H-21PR
Aprilaire®	8465

